



## NK IBEX

### GENERAL SPECIFICATIONS

**POST SYSTEM:** RHS posts at 3.025m centres, panel fixed to post with 25 x 5mm slotted clamp bar using NK M8 tamper – resistant bolt and threaded nutserts.

**PANEL WIDTH:** 3079mm

**FINISH:** Galvanised and polyester powder coated to BS EN 13438-2005 in a range of colours to suit your individual requirements.

FENCE Ht (m)	POST SECTION	NUMBER OF BEAMS	NUMBER OF FIXINGS	PANEL WEIGHT
1.2	60x60	2	4	21kg
1.85	60x60	4	5	34kg
2.05	60x60	4	6	37kg
2.45*	60x60	4	7	43kg
3.05*	80x80	6	9	55kg

\* Multi-lift panels - 1.85 with 1.2 above. # With protruding points

**APPLICATION:** NK IbeX Vogue is a general purpose fencing system for boundary demarcation and aesthetic perimeters. NK IbeX Vogue offers an attractive decorative choice, suitable for both recreational and commercial properties.

**KEY FEATURES:** NK IbeX Vogue is a robust and high density mesh fencing system with varying apertures. Vertical wire spacing forms a 6 : 1 : 6 pattern which creates a textured visual effect on the facade. Panel heights greater than 2.05m offer 22mm protruding wire ends on the top edge to provide an increased security enhancement. Installation of all fencing is subject to site specific risk assessments and NK recommends due regard should be given to nearby aids to scaling or natural overhangs.

NK IbeX Vogue - adding a touch of class to your perimeter.

### RELATED PRODUCTS

**SWINGING AND SLIDING GATES:** Single and Double Leaf Swinging and Sliding Gates are available in a range of standard widths to suit your individual requirements, with manual or automated control.

#### OTHER PRODUCTS:

- ▶ NK IbeX Elite
- ▶ NK IbeX Supreme
- ▶ NK IbeX Premier
- ▶ NK IbeX Premier Plus
- ▶ NK IbeX Security
- ▶ NK IbeX Hi-Security

### STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

**BLACK**  
RAL 9005

**GREY**  
RAL 7037

**BLUE**  
RAL 5010

**WHITE**  
RAL 9010

**GREEN**  
RAL 6005

**RED**  
RAL 3000

**YELLOW**  
RAL 1006

**BROWN**  
RAL 8019