



NK ACCESS CONTROL

GENERAL SPECIFICATIONS

Cantilevered Sliding gate leaves, framework construction comprising 75 x 75mm SHS with 250 x 225mm deep extruded aluminium bottom section.

INFILL: 30mm diameter x 6mm wall thickness.

AVAILABLE HEIGHTS: 1.2m, 1.8m, 2.0m and 2.4m.

AVAILABLE WIDTHS: 3m up to 10m in 500mm increments. If gates are of double leaf construction the available widths are twice the above.

OPERATION TIME: 4 seconds per metre (variable).

POWER UNIT: Friction-driven 3 phase motor.

STANDARD CONTROL: 1 Nr deadmans keyswitch to inside of cabinet, 1 Nr Radio receiver and 2 Nr remote handheld transmitters, 1 Nr seven day timer.

STANDARD SAFETY: 6 Nr safety edges, dual height photocells to inside of support steelwork.

KEY FEATURES: The NK Salvus sliding gate guarantees smooth, consistent and quiet gate movement, as a result of the revolutionary external friction drive mechanism.

A securely concealed manual release mechanism is included as standard allowing manual control of the gate in the event of a power failure.

The NK Salvus is fully compliant with BS/EN 12453 safety features as directed from the European Standards and Regulations.

As an additional deterrent to climbing or scaling the 2.0m and 2.4m high range come complete as standard with a serrated top.

ADDITIONAL ITEMS: Safety Options: Flashing light, Open close stop console.

Control Options: Stainless steel Intercom, Stainless steel Videocom, Stainless steel key pad, Stand alone prox reader, Network prox reader and additional Hand held radio Transmitters.

RELATED PRODUCTS

OTHER PRODUCTS:

- ▶ NK Automated Swinging Gates
- ▶ NK Turnstiles
- ▶ NK Automated Traffic Barriers
- ▶ NK Bollards
- ▶ NK Swinging Barriers
- ▶ NK Self-Closing Safety Gates

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019